


# GPS and Surveying of Weed Populations *Equipment and Costs*

By: Pat Akers, Integrated Pest Control Branch,  
California Dept. of Food and Agriculture



Scott Park uses a GPS unit to measure a *Lygodium* infestation in the Big Cypress Seminole Indian Reservation in Florida. Photo by John Volin.



filtering and calculations. The second major component is a set of 24 specialized satellites that the

GPS receiver uses for calculating its position. The third component is a set of ground stations for tracking the satellites. Each satellite broadcasts several different sets of information, of which three are most important to our discussion: 1) a time signal, 2) information on the satellites' positions, and 3) a unique binary sequence code (C/A). By receiving the satellite signals, the GPS receiver can triangulate its position by calculating its distance from each satellite. *For an expanded description of different sets of information see [www.cdfa.ca.gov/gps](http://www.cdfa.ca.gov/gps).*

## Effects of the System on the Field User

The characteristics of the system have at least four major effects on its use in the field: 1) Ninety-five percent of the time, the system (itself) will estimate a position within about 22 meters of the true position. The Department of Defense adds an additional error signal to the system, degrading its accuracy to about 100 meters. This makes the accuracy of an expensive GPS about the same as a low-end model. 2) The receiver has to be able to lock onto at least four satellites in order to determine a position in three dimensions. 3) Trees, hills or buildings can obscure the satellite signals. 4) At times, the satellites will be clustered in one small part of the sky. Such an arrangement can seriously degrade the accuracy of the position

calculations. Some GPS units will stop collecting data under such conditions, and all you can do is wait 20-40 minutes until the satellites move into a better arrangement.

## Choosing a GPS Unit: Juggling Needs

The selection of a GPS unit will strongly depend on the needs of the user. Examples of common user needs are:

- 1) Accuracy for navigation.
- 2) Accuracy for detailed mapping (with 2-3 meter accuracy being adequate).
- 3) Accuracy without having to remain on a single location for more than 1 second.
- 4) The GPS data must be easily transferred to a mapping program (Geographic Information System or GIS).
- 5) The ability to record specific descriptive information along with the positional data.
- 6) The unit should be as convenient to use as possible.
- 7) Costs should be kept as low as possible. Meeting different requirements affects the cost of the GPS solution.

**Low-end Systems** - The absolutely lowest cost option is one of the many sportsman GPS models on the market. Many of these units are highly sophisticated, very portable, offer a number of convenient bells and whistles, and cost less than \$300, sometimes as little as \$200. For example, both Garmin and Eagle manufacture 12-parallel-channel GPS units which have received good

Nowadays most people are probably aware of the existence of the Global Positioning System, better known as GPS. Many know that it's useful for surveying, agriculture, mining, geology, navigating and locating objects on the earth. In fact, GPS has found many important uses in natural resource management, including the mapping of weed populations. This article describes the selection of GPS equipment for the mapping and management of weeds.

## A Primer on How it Works

GPS has three major components. The first component is the GPS unit, which gives us access to the system. A GPS unit is a specialized radio receiver combined with electronics for

reviews from users. These systems are limited to 100 meter accuracy unless differentially corrected. Although many of these units describe themselves as “DGPS ready,” an antenna and receiver for the correction data must be added separately. They also have limited capabilities to store GPS position information, especially descriptive data.

The next important improvement is the addition of differential correction capability. There are a lot of options, with lots of trade-offs. However, the issue is further complicated because Trimble’s “mapping-quality” GPS units all provide essentially a complete mapping package, including the ability to differentially correct data using PPDGPS. Since there is almost a qualitative divide between them and other GPS systems, I will treat Trimble products separately.

***Trimble vs. Everybody Else: “Mapping Grade” GPS systems*** - Trimble mapping products are expensive, but they provide mapping data with 0.5-3 meter accuracy, using a standard computer

and Internet connection. Their system includes software (Pathfinder Office) that runs on the PC computer and provides a powerful and easy PPDGPS facility. The package provides reasonably flexible data entry capabilities, the ability to record information on line-type or area-type objects (instead of just points), and flexible integration with GIS systems.

Trimble has essentially two lines that depend on PPDGPS. 1) *Trimble’s GeoExplorer* is a hand-held GPS that costs about \$3500 with the battery pack. It provides 1-3 meter accuracy, differentially corrected. It has a fairly flexible data entry capability and it’s controlled through a series of menus, but it has only 8 buttons on the keypad. Text data is entered by scrolling through the entire alphanumeric character set, which can be quite tedious. Fortunately, the data entry screens allow the creation of menus, which can often minimize the need to enter text. 2) *Trimble’s Pathfinder Pro XL* has the GPS receiver mounted in a backpack, attached to a handheld datalogger, and its 8- or 12-channel GPS engine pro-

vides accuracy to less than a meter. Trimble no longer manufactures it, but it can often be found used. The updated versions of the ProXL are the ProXR and ProXRS, which integrate RTDGPS capability and provide accuracy down to 0.5 meters. They cost \$9,000 to \$12,000. The “ProX” line dataloggers provides better information about the GPS status than the GeoExplorer and they have full alphanumeric keypads. *For further discussion see [www.cdfa.ca.gov/gps](http://www.cdfa.ca.gov/gps).*

***And for Everybody Else: Real Time Differential GPS (RTDGPS)*** - RTDGPS has one big advantage over Post-Processed Differential GPS (PPDGPS): the corrected, high-accuracy results are available immediately in the field. This makes RTDGPS extremely useful for navigation, as its accuracy is 1-20 meters, depending on the quality of the receiver and the reference data. The major disadvantage of RTDGPS relative to PPDGPS is that the accurate results depend on remaining in contact with the reference station. Any locations recorded while out of contact will



USDA researchers use GPS technology to track the progress of the country's first melaleuca biocontrol agent, *Oxyops vitiosa* in Florida.

have only 100 meter accuracy, and there will be no way to improve that accuracy, either in the field or the office (unless you also have PPDGPS capability, or want to stay on one location for an extended period of time so you can average the results). PPDGPS does not depend on remaining in contact with a reference station. RTDGPS is also somewhat less accurate than PPDGPS, but the difference is generally negligible for all but the most demanding applications. In the past, RTDGPS had other disadvantages having to do with the complexity and expense of implementing RTDGPS relative to PPDGPS, especially for implementing the most dependable solutions. However, as with most emerging technologies, costs continue to drop and performance improves. In the last year or so RTDGPS solutions have begun to appear that approach the cost-effectiveness and dependability of Trimble units.

The major variable in the cost vs. dependability equation of RTDGPS is the choice of the source for the differential correction data. For most of us, there are three major sources for correction data: 1) commercial broadcasts on FM wavelengths, using transmission facilities of normal commercial

radio, 2) commercial broadcasts from geosynchronous satellites, and 3) government broadcasts from specialized Coast Guard DGPS transmitters called "Beacons." As you might expect, there are trade-offs between cost, convenience, and capability for these different options. *For a more complete discussion of sources for data correction see [www.cdfa.ca.gov/gps](http://www.cdfa.ca.gov/gps)*

**Mix and Match** - There are two other trends that can affect the choice of a system. First, RTDGPS has such overpowering advantages that manufacturers are integrating RTDGPS receivers with GPS receivers in their higher-end systems. For example, *Trimble's ProXL* has been replaced by the ProXR, which incorporates a Beacon receiver, and the ProXRS, which incorporates both a Beacon and satellite receiver. The other trend is to turn a computer or other equipment into a GPS system. For instance, TeleType produces a small GPS sensor, without any readout whatsoever, that can plug into the PC port of a laptop computer and turn it into a GPS unit. Including software to allow viewing of the results against a background map, it costs about \$850. At Cdfa, we are about to evaluate a similar system. It combines a Racal Navigator 2-meter accuracy DGPS sensor (which is a Trimble 8-channel GPS receiver integrated with Racal's DGPS correction receiver), a handheld Windows CE computer, and datalogging/GPS/mapping software to create a complete datalogging RTDGPS system, which should also provide a moving map for navigation purposes. The sensor costs about \$2800, the handheld computer about \$600, the software about \$700, and various costs for cables, battery, and pack bring the total cost to \$4500, which includes one year of the satellite DGPS subscription service. This competes in cost with the GeoExplorer, yet provides real-time differential GPS in the field for excellent navigation (especially with the moving map), robust satellite service, and a very convenient and flexible data entry system.

### What's a Poor Mapper to Do?

If you are trying to get into GPS mapping of weeds, the first step is to

## XenoNET

### General GPS Web Sites

[www.navcen.uscg.mil/dgps](http://www.navcen.uscg.mil/dgps) -The Coast Guard site for DGPS  
[www.fs.fed.us/database/gps/](http://www.fs.fed.us/database/gps/) USFS -GPS Page, especially good for access to Trimble Base Station sites  
[ftp://ftp.trimble.com/pub/cbsfiles/](http://ftp://ftp.trimble.com/pub/cbsfiles/) -Trimble's base station files from Sunnyvale, CA  
[www.fs.fed.us/database/gps/eureka.htm](http://www.fs.fed.us/database/gps/eureka.htm) -USFS Eureka, California GPS base station  
[www.cnde.iastate.edu/staff/swormley/gps/dgps.html](http://www.cnde.iastate.edu/staff/swormley/gps/dgps.html) -Sam Wormley's DGPS explanations  
[www.qualityeng.co.uk/gpstutor](http://www.qualityeng.co.uk/gpstutor) -GPS Tutor: fairly detailed treatment  
[vancouver-webpages.com/pub/peter/index.html](http://vancouver-webpages.com/pub/peter/index.html) -Peter Bennett's GPS and NMEA Site  
[www.geo.swt.edu/reference/Gps.html](http://www.geo.swt.edu/reference/Gps.html) -GPS LINKS  
[www.gislinc.com/GPS\\_Sites/](http://www.gislinc.com/GPS_Sites/) -Gateway site for links to many GPS and GIS issues  
[www.utexas.edu/depts/grg/gcraft/notes/gps/gps.html](http://www.utexas.edu/depts/grg/gcraft/notes/gps/gps.html) -GPS overview  
[www.trimble.com/gps/index.htm](http://www.trimble.com/gps/index.htm) -Trimble GPS overview

### GPS "General Stores"

[www.navtechgps.com](http://www.navtechgps.com) -Navtech GPS Store  
[www.cansel.ca](http://www.cansel.ca) -Cansel: sales and rentals  
 GPS and surveying equipment  
[www.geowarehouse.com](http://www.geowarehouse.com) -Geowarehouse  
[www.nvlt.com/index.html](http://www.nvlt.com/index.html) -NVLT GPS Receivers and Satellite Communication Products

### Mapping and Surveying Grade GPS Manufacturers

[www.trimble.com](http://www.trimble.com) -Trimble GPS Solutions  
[www.cmtinc.com](http://www.cmtinc.com) -Corvallis Microtechnology, Inc  
[www.satloc.com/index.stm](http://www.satloc.com/index.stm) -Satloc: especially for agricultural applications, but also mapping  
[www.ashtech.com](http://www.ashtech.com) -Ashtech, now merged with Magellan  
[www.topcon.com](http://www.topcon.com) -Topcon, mostly surveying

### Consumer-grade GPS Manufacturers (including Beacon RTDGPS receivers)

[www.eaglegps.com](http://www.eaglegps.com) -Eagle Electronics  
[www.garmin.com](http://www.garmin.com) -Garmin GPS products  
[www.magellangps.com](http://www.magellangps.com) -Magellan GPS products

### Vendors of FM RTDGPS receivers and services

[www.accqpoint.com](http://www.accqpoint.com) -ACCQPOINT Communications Corporation  
[www.dgps.com](http://www.dgps.com) -DCI's DGPS and TMC Services

### Vendors of Satellite RTDGPS receivers and services

[www.omnistar.com](http://www.omnistar.com) -OmniStar  
[www.racal-landstar-usa.com](http://www.racal-landstar-usa.com)  
[www.racal-landstar.com](http://www.racal-landstar.com) -Racal LandStar

### Post-Processing DGPS Software

[www.geotronics.se:81/gpssoft.shtml](http://www.geotronics.se:81/gpssoft.shtml) -Geotracer System 2000



establish your priorities, including cost. Your budget will determine whether you can afford differential correction and flexible data entry and manipulation. Also consider where you work. If you work within range of the Coast Guard Beacons, this is definitely an option to consider carefully. A simple sportsman model GPS with an added consumer-level Beacon receiver (accurate to 4-12 meters) would not cost much more than \$600 total. For another \$1100-1500 you could add flexible data entry, by interfacing a Beacon-based RTDGPS sensor with a consumer handheld computer and appropriate software. If you work beyond the range of the Beacons but have a higher budget, *Trimble's GeoExplorer* provides data entry flexibility, good accuracy for mapping via PPDGPS, and no continuing subscription costs. If you can afford an additional \$800 per year above the cost of a *GeoExplorer*, then a handheld computer system interfaced with a satellite-based RTDGPS will give you accurate navigation, very convenient data entry, and the freedom of satellite RTDGPS. If you cannot afford differential correction, probably greater overall accuracy can be

achieved with careful marking of 7.5 min USGS topographic quads in the field, rather than GPS. Finally, remember that GPS is an emerging technology. If you can't afford what you want now, in a year or two it might be available.

### **Improving the Accuracy of the GPS System: Differential Correction**

Most of us would probably wish to locate a weed to better than 100 meters, or even 20 meters. There are several ways of improving the accuracy of the GPS system, but the one that presently offers the best combination of speed, convenience, cost, and dependability is called differential correction, or differential GPS (DGPS). It is not the most accurate, but will provide 0.5-10 meter accuracy with one second of data, depending on the quality of the GPS receiver. Even the better sportsman models routinely provide 2-5 meter accuracy using differential correction. One to three meters of accuracy has proved adequate for our needs at CDFA, and DGPS has so many other advantages over more accurate ap-

proaches that we have never implemented them.

DGPS works on a simple principle. One unit is stationary, at a known location, and acts as a reference base station. The base station unit knows its true location, but continues to calculate its position according to the information it receives from the GPS satellites. The difference between the calculated position and the true position provides an accurate estimate of the errors in the calculated measurement, at the time of the measurement. This estimate of the error can then be applied to the position calculations made at the same time by any GPS unit nearby (called the mobile or rover unit), even if it is moving. For many applications, "nearby" can be anywhere up to 200 miles.

There are two major methods whereby differential corrections can be applied to the measurements made by a mobile unit. 1) **Post-Processed DGPS (PPDGPS)**: The position measurements are stored in the mobile GPS and later downloaded to a computer. The correction measurements from the reference GPS are also downloaded into the computer, and then specialized

software applies the corrections to the measurements made by the mobile unit. 2) **Real-Time DGPS (RTDGPS):** The correction measurements from the reference GPS are sent to the mobile GPS (almost always by radio), and the corrections are applied to the position measurements a split second after they are made. The mobile GPS unit must have the necessary software and circuitry to apply the corrections to the mobile GPS position measurements, but this capability is now common in modern GPS units, even many sportsman models. Such models use phrases such as “DGPS ready” to describe themselves. A separate antenna and receiver must be added to the GPS unit so it can receive the broadcasts from the reference station. In addition, in many cases access to the reference station signals is sold as a separate service. In high-end professional GPS units, integrated receivers for the reference stations are becoming more common.

*Pat Akers is a Agricultural Biologist with the Integrated Pest Control Branch, California Department of Food and Agriculture, [pakers@cdfa.ca.gov](mailto:pakers@cdfa.ca.gov)*